General stability criteria for inviscid rotating flow *

Liang Sun†
School of Earth and Space Sciences, University of Science and Technology of China, Hefei 230026, China.
and LASG, Institute of Atmospheric Physics, Chinese Academy of Sciences, Beijing 100029, China.
(Dated: May 12, 2010)

The general stability criteria of inviscid Taylor-Couette flows with angular velocity $\Omega(r)$ are obtained analytically. First, a necessary instability criterion for centrifugal flows is derived as $\xi'(\Omega-\Omega_s)<0$ (or $\xi'/(\Omega-\Omega_s)<0$) somewhere in the flow field, where ξ is the vorticitiy of profile and Ω_s is the angular velocity at the inflection point $\xi'=0$. Second, a criterion for stability is found as $-(\mu_1+1/r_2)<f(r)=\frac{\xi'}{\Omega-\Omega_s}<0$, where μ_1 is the smallest eigenvalue. The new criteria are the analogues of the criteria for parallel flows, which are special cases of Arnol'd's nonlinear criteria. Specifically, Pedley's cirterion is proved to be an special case of Rayleigh's criterion. Moreover, the criteria for parallel flows can also be derived from those for the rotating flows. These results extend the previous theorems and would intrigue future research on the mechanism of hydrodynamic instability.

PACS numbers: 47.32.-y, 47.20.-k, 97.10.Gz

arXiv:physics/0603177v3 [physics.flu-dyn] 11 May 2010

The instability of the rotating flows is one of the most attractive problems in many fields, such as fluid dynamics, astrophysical hydrodynamics, oceanography, meteorology, etc. Among them, the simplest one is the instability of pure rotation flow between coaxial cylinders, i.e., Taylor-Couette flow, which has intensively been explored [1, 2].

Two kinds of instabilities in inviscid rotating flow have been theoretically addressed in the literatures. One is centrifugal instability, which was first investigated by Rayleigh [2, 3]. He derived the circulation criterion for the inviscid rotating flows that a necessary and sufficient condition for stability to axisymmetric disturbances is that the square of the circulation does not decrease anywhere. This criterion is also be stated as the Rayleigh discriminant $\Phi\geq 0$ (see Eq.(5) behind), and is always be used in astrophysical hydrodynamics. It is also generalized to non-axisymmetric flows [4]. The other is known as instability due to two-dimensional disturbances in rotating flows, which is similar to the shear instability in parallel flow. We call this instability as the shear instability in rotating flow hereafter. For this instability, Rayleigh also obtained a criterion, i.e., inflection point theorem in inviscid rotating flows, which is the analogue of the theorem in parallel flows [3]. Following this way, Howard and Gupta [5] found a stability criterion for two-dimensional disturbance in inviscid rotating flow. However, the theoretical results remains scarce, due to the complexity of rotating flow.

Comparing the instability in the rotating flow with shear instability in parallel flows, the criteria for parallel flows are much more abundant. Fjørtoft [6] and Sun [7, 8] proved some more strict criteria. And the stability of two-dimensional in a rotating frame was also addressed by Pedley [9], which seems to be more complex than the stability problem in the pure rotation flows.

Motivated, then, by the theoretical criteria for parallel flows [6, 7], our study focuses on the instability due to shear in inviscid rotating flows. The aim of this letter is to obtain such criteria for the inviscid rotating flows, and the relationship between previous criteria is also discussed. Thus other instabilities may be understood via the investigation here.

For this purpose, Howard-Gupta equation (hereafter H-G equation) [5] is employed. To obtain H-G equation, Euler's equations [1, 2, 10] for incompressible barotropic flow in cylindrical polar coordinates (r,θ) are then given by

$$\frac{\partial u_r}{\partial t}+u_r\frac{\partial u_r}{\partial r}+\frac{u_\theta}{r}\frac{\partial u_r}{\partial\theta}-\frac{u_\theta^2}{r}=-\frac{1}{\rho}\frac{\partial p}{\partial r}, \tag{1}$$

and

$$\frac{\partial u_\theta}{\partial t}+u_r\frac{\partial u_\theta}{\partial r}+\frac{u_\theta}{r}\frac{\partial u_\theta}{\partial\theta}+\frac{u_r u_\theta}{r}=-\frac{1}{\rho r}\frac{\partial p}{\partial\theta}. \tag{2}$$

Under the condition of incompressible barotropic flow, the evolution equation for the vorticity can be obtained from Eq.(1) and Eq.(2),

$$\frac{\partial\xi}{\partial t}+u_r\frac{\partial\xi}{\partial r}+\frac{u_\theta}{r}\frac{\partial\xi}{\partial\theta}=0, \tag{3}$$

where $\xi=\frac{1}{r}\frac{\partial}{\partial r}(ru_\theta)-\frac{1}{r}\frac{\partial u_r}{\partial\theta}$ is the vorticity of the background flow. Eq.(3) can also be derived from Fridman's vortex dynamics equation [11, 12]. And it admits a steady basic solution,

$$u_r=0, u_\theta=V(r)=\Omega(r)r, \tag{4}$$

where $\Omega(r)$ is the mean angular velocity. And Rayleigh discriminant is defined by

$$\Phi=\frac{1}{r^3}\frac{d}{dr}(\Omega r^2)^2. \tag{5}$$

*This work is supported by the National Foundation of Natural Science (No. 40705027), the Knowledge Innovation Program of the Chinese Academy of Sciences (Nos. KZCX2-YW-QN514), and the National Basic Research Program of China (No. 2007CB816004).
†Electronic address: sunl@ustc.edu.cn; sunl@ustc.edu

Then, consider the evolution of two-dimensional disturbances. The disturbances $\psi'(r,\theta,t)$, which depend only on r, θ and t, expand as series of waves,

$$\psi'(r,\theta,t) = \phi(r)e^{i(n\theta-\omega t)}, \tag{6}$$

where $\phi(r)$ is the amplitude of disturbance, n is real wavenumber and $\omega = \omega_r + i\omega_i$ is complex frequency. Unlike the wavenumber in Rayleigh's equation for inviscid parallel flows, the wavenumber n here must be integer for the periodic condition of θ. The flow is unstable if and only if $\omega_i > 0$. In this way, the amplitude ϕ satisfies

$$(n\Omega-\omega)[D^*D - \frac{n^2}{r^2}]\phi - \frac{n}{r}(D\xi)\phi = 0, \tag{7}$$

where $D = d/dr$, $D^* = d/dr + 1/r$. This equation is known as H-G equation and to be solved subject to homogeneous boundary conditions

$$D\phi = 0 \ at \ r = r_1, r_2. \tag{8}$$

By multiplying $\frac{r\phi^*}{\omega-\Omega n}$ to H-G equation Eq.(7), where ϕ^* is the complex conjugate of ϕ, and integrating over the domain $r_1 \le r \le r_2$, we get the following equation

$$\int_{r_1}^{r_2} r\{\phi^*(D^*D)\phi - [\frac{n^2}{r^2} + \frac{nD(\xi)}{r(n\Omega-\omega)}]\|\phi\|^2\}dr \ = 0. \tag{9}$$

Then the integration gives

$$\int_{r_1}^{r_2} r\{\|\phi'\|^2 + [\frac{n^2}{r^2} + \frac{n(\Omega n-\omega^*)\xi'}{r\|\Omega n-\omega\|^2}]\|\phi\|^2\}dr \ = 0, \tag{10}$$

where $\phi' = D\phi$, $\xi' = D(\xi)$ and ω^* is the complex conjugate of ω. Thus the real part and image part are

$$\int_{r_1}^{r_2} r\{\|\phi'\|^2 + [\frac{n^2}{r^2} + \frac{(\Omega-c_r)\xi'}{r\|\Omega-c\|^2}]\|\phi\|^2\}dr = 0, \tag{11}$$

and

$$\int_{r_1}^{r_2} \frac{c_i\xi'}{\|\Omega-c\|^2}\|\phi\|^2 dr \ = 0, \tag{12}$$

where $c = \omega/n = c_r + ic_i$ is the complex angular phase speed. Rayleigh used only Eq.(12) to prove his theorem: The necessary condition for instability is that the gradient of the basic vorticity ξ' must change sign at least once in the interval $r_1 < r < r_2$. The point at $r = r_s$ is called the inflection point with $\xi'_s = 0$, at which the angular velocity of $\Omega_s = \Omega(r_s)$. This theorem is the analogue of Rayleigh's inflection point theorem for parallel flow [2, 3].

Similar to the proof of Fjørtoft theorem [6] in the parallel flow, we can prove the following criterion.

Theorem 1: A necessary condition for instability is that $\xi'(\Omega-\Omega_s) < 0$ (or $\xi'/(\Omega-\Omega_s) < 0$) somewhere in the flow field.

The proof of Theorem 1 is trivial, and is omitted here. This criterion is more restrictive than Rayleigh's. Moreover, some more restrictive criteria may also be found, if we follow the way given by Sun [7]. If the velocity profile $\Omega(r)$ is stable ($c_i = 0$), then the hypothesis $c_i \neq 0$ should result in contradictions in some cases. So that a more restrictive criterion can be obtained.

To find the criterion, we need estimate the rate of $\int_{r_1}^{r_2} r\|\phi'\|^2 dr$ to $\int_{r_1}^{r_2} \|\phi\|^2 dr$,

$$\int_{r_1}^{r_2} r\|\phi'\|^2 dr = \mu \int_{r_1}^{r_2} \|\phi\|^2 dr, \tag{13}$$

where the eigenvalue μ is positive definition for $\phi \neq 0$. According to boundary condition Eq.(8), ϕ can expand as Fourier series. So the smallest eigenvalue, namely μ_1, can be estimated as $\mu_1 > r_1\pi^2/(r_2-r_1)^2$ [7, 13].

Then there is a criterion for stability using relation (13), a new stability criterion may be found: the flow is stable if $-(\mu_1 + 1/r_2) < \frac{\xi'}{\Omega-\Omega_s} < 0$ everywhere.

To get this criterion, we introduce an auxiliary function $f(r) = \frac{\xi'}{\Omega-\Omega_s}$, where $f(r)$ is finite at inflection point. We will prove the criterion by two steps. At first, we prove proposition 1: if the velocity profile is subject to $-(\mu_1 + 1/r_2) < f(r) < 0$, then $c_r \neq \Omega_s$.

Proof: Since $-(\mu_1 + 1/r_2) < f(r) < 0$, then

$$-(\mu_1 + 1/r_2) < \frac{\xi'}{\Omega-\Omega_s} \le \frac{\xi'(\Omega-\Omega_s)}{(\Omega-\Omega_s)^2 + c_i^2}, \tag{14}$$

and if $c_r = \Omega_s$ and $1 \le n$, this yields to

$$\begin{aligned} &\int_{r_1}^{r_2} r\|\phi'\|^2 + [\frac{n^2}{r} + \frac{\xi'(\Omega-\Omega_s)}{\|\Omega-c\|^2}]\|\phi\|^2 \, dr \ \ge \\ &\int_{r_1}^{r_2} [(\mu_1 + \frac{1}{r_2}) + \frac{1}{r} + \frac{\xi'}{(\Omega-\Omega_s)}]\|\phi\|^2 dr \ > 0. \end{aligned} \tag{15}$$

This contradicts Eq.(11). So proposition 1 is proved.

Then, we prove proposition 2: if $-(\mu_1+1/r_2) < f(r) < 0$ and $c_r \neq \Omega_s$, there must be $c_i^2 = 0$.

Proof: If $c_i^2 \neq 0$, then multiplying Eq.(12) by $(c_r - c_t)/c_i$, where the arbitrary real number c_t does not depend on r, and adding the result to Eq.(11), it satisfies

$$\int_{r_1}^{r_2} r\{\|\phi'\|^2 + [\frac{n^2}{r^2} + \frac{\xi'(\Omega-c_t)}{r\|\Omega-c\|^2}]\|\phi\|^2\} \, dr = 0. \tag{16}$$

But the above Eq.(16) can not be hold for some special c_t. For example, let $c_t = 2c_r - \Omega_s$, then there is $(\Omega - \Omega_s)(\Omega - c_t) < \|\Omega - c\|^2$, and

$$\frac{\xi'(\Omega-c_t)}{\|\Omega-c\|^2} = f(r)\frac{(\Omega-\Omega_s)(\Omega-c_t)}{\|\Omega-c\|^2} > -(\mu_1 + \frac{1}{r_2}). \tag{17}$$

This yields

$$\int_{r_1}^{r_2} [r\|\phi'\|^2 + (\frac{n^2}{r} + \frac{\xi'(\Omega-c_t)}{\|\Omega-c\|^2})\|\phi\|^2]dr > 0, \tag{18}$$

which also contradicts Eq.(16). So the second proposition is also proved.

Using 'proposition 1: if $-(\mu_1 + 1/r_2) < f(r) < 0$ then $c_r \neq \Omega_s$' and 'proposition 2: if $-(\mu_1 + 1/r_2) < f(r) < 0$ and $c_r \neq \Omega_s$ then $c_i = 0$', we find a stability criterion.

Theorem 2: If the velocity profile satisfy $-(\mu_1 + 1/r_2) < f(r) < 0$ everywhere in the flow, it is stable.

This criterion is the analogue of the theorem proved by Sun [7]. Both theorem 1 and theorem 2 here are more restrictive than Rayleigh's theorem for the inviscid rotating flows. The theorems indicate the probability that a vorticity profile with local maximum or minimum would be stable, if it satisfies the stable criteria. Theorem 2 implies that the rotating flow is stable, if the distribution of vorticity is relatively smooth. As shown by Sun [7], the instability of inviscid parallel flows must have vortices concentrated enough. This is also the shear instability in rotating flows. Since several stable criteria for inviscid rotating flows have been obtained, it is convenient to explore the relationship among them, as discussed followed.

The criteria for rotating flow can be applied to parallel flows, given narrow-gap approximation. First, Pedley's criterion is covered by the centrifugal instability criteria. As mentioned above, Pedley [9] considered the stability of two-dimensional flows U in a frame rotating with angular velocity Ω. A criterion is found that instability occurs locally when $2\Omega(2\Omega - U') < 0$, where $U' = dU/dr$ represents radial shear of horizontal velocity. Pedley's criterion, which is recovered by later researches [14, 15], is in essence the special case of Rayleigh's circulation criterion, i.e., $\frac{d}{dr}(\Omega^2 r^4) < 0$ for instability. Here the proof is briefly given. Considering the narrow-gap approximation $r_2 - r_1 = d \ll r_1$ and the large radii approximation $1/r_1 \to 0$ in Rayleigh's circulation criterion, there is $\Omega' r \approx -U'$. So $\Phi = d(\Omega^2 r^4)/dr/r^3 = 2\Omega(2\Omega - U') < 0$, which is exactly Pedley's criterion. Thus Pedley's criterion is covered by Rayleigh's circulation criterion. Second, the stable criteria for parallel flows, such as Rayleigh's theorem [3] and Fjørtfot's theorem [6], can be derived from those for rotating flows, given the narrow-gap approximation $r_2 - r_1 = d \ll r_1$ and the large radii approximation $1/r_1 \to 0$. Following this way, the results of the Taylor-Couette system can also be applied to the plane Couette system [16]. The proof is omitted here, as the approach is trivial too. As pointed out by Sun [7], all of the shear instability criteria for two-dimensional flows are the special cases of Arnol'd's nonlinear criteria [17], which are much more complex yet not widely used. In general, all the known stability criteria for parallel flows (even in a rotating frame) can be derived from the stability criteria for rotating flows.

In summary, the general stability criterion is obtained for inviscid rotating flow. These results extend Rayleigh's inflection point theorem for curved and rotating flows, and they are analogues of the theorems proved by Fjørtoft and Sun for the two-dimensional inviscid parallel flows. Then Pedley's cirterion is proved to be an special case of Rayleigh's criterion. Moreover, the theorems for the parallel flows can be derived from those for the rotating flows, given narrow-gap and large radii approximations. These criteria extend the previous results and would intrigue future research on the mechanism of hydrodynamic instability.

[1] S. Chandrasekhar, *Hydrodynamic and Hydromagnetic Stability* (Dover Publications, Inc., New York, U.S.A., 1961).
[2] P. G. Drazin and W. H. Reid, *Hydrodynamic Stability* (Cambridge University Press, 2004).
[3] L. Rayleigh, Proc. London Math. Soc. **11**, 57 (1880).
[4] B. Paul and G. Francois, J. Fluid Mech. **542**, 365 (2005).
[5] L. N. Howard and A. S. Gupta, J. Fluid Mech. **14**, 463 (1962).
[6] R. Fjørtoft, Geofysiske Publikasjoner **17**, 1 (1950).
[7] L. Sun, Eur. J. Phys. **28**, 889 (2007).
[8] L. Sun, Chin. Phys. Lett. **25**, 1343 (2008).
[9] T. J. Pedley, J. Fluid Mech. **35**, 97 (1969).
[10] W. O. Criminale, T. L. Jackson, and R. D. Joslin, *Theory and computation of hydrodynamic stability* (Cambridge University Press, Cambridge, U.K., 2003).
[11] G. K. Batchelor, *An Introduction to Fluid Dynamics* (Cambridge University Press, Cambridge, U. K., 1967).
[12] P. G. Saffman, *Vortex Dynamics* (Cambridge University Press, Cambridge, U.K., 1992).
[13] M. Mu, Q. C. Zeng, T. G. Shepherd, and Y. M. Liu, J. Fluid Mech. **264**, 165 (1994).
[14] S. Leblanc and C. Cambon, Phys. Fluids **9(5)**, 1307 (1997).
[15] D. J. Tritton, J. Fluid Mech. **241**, 503 (1992).
[16] H. Faisst and B. Eckhardt, Phys. Rev. E. **61**, 7227 (2000).
[17] V. I. Arnold, Amer. Math. Soc. Transl. **19**, 267 (1969).